

# SlowStop® Energy Absorbing Bollard – Type 2 (SS-T2Y-100)



[www.slowstop.eu](http://www.slowstop.eu)

Our workhorse model for distribution centers and general industry.  
Recommended for fork lifts up to 5000 kg lift capacity.

Color: RAL 1023 Yellow Bollard on RAL 9005 Black Base

Diameter: 101,6mm (6,3 mm wall)

Height: 100 cm

Set Screws: 5 M16 x 2,00  
8mm Hex

Cap: Black Plastic

Installs with four (4)  
Concrete Anchor Screws



| MASS (KG)   | 1000 | 2000 | 3000 | 4000 | 5000 | 6000 | 7000 | 8000 | 9000 | 10000 | 15000 |
|-------------|------|------|------|------|------|------|------|------|------|-------|-------|
| SPEED (KPH) |      |      |      |      |      |      |      |      |      |       |       |
| 3.0         |      |      |      |      |      |      |      |      |      |       |       |
| 3.5         |      |      |      |      |      |      |      |      |      |       |       |
| 4.0         |      |      |      |      |      |      |      |      |      |       |       |
| 4.5         |      |      |      |      |      |      |      |      |      |       |       |
| 5.0         |      |      |      |      |      |      |      |      |      |       |       |
| 5.5         |      |      |      |      |      |      |      |      |      |       |       |
| 6.0         |      |      |      |      |      |      |      |      |      |       |       |
| 6.5         |      |      |      |      |      |      |      |      |      |       |       |
| 7.0         |      |      |      |      |      |      |      |      |      |       |       |
| 7.5         |      |      |      |      |      |      |      |      |      |       |       |
| 8.0         |      |      |      |      |      |      |      |      |      |       |       |
| 8.5         |      |      |      |      |      |      |      |      |      |       |       |
| 9.0         |      |      |      |      |      |      |      |      |      |       |       |
| 9.5         |      |      |      |      |      |      |      |      |      |       |       |

No Damage / Negligible Damage  
Will Stop / Potential Damage to Guard  
Guard is under-sized

### SPECIFICATIONS

- Stopping Power Rating: 5.334 joules
- Temperature Rating: -40° to 70°C
- Pipe Coating: EN-ISO 1461 Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat. C5I corrosion resistance.
- Frangible base eliminates floor damage. Safe for structural concrete.

### RECOMMENDED USES



- Powered Industrial Trucks to 5000 kg lift capacity
- Equipment and Storage Rack Guarding
- Door and Wall Protection
- Utility Protection
- Pedestrian Safety
- Parking Facilities
- Fuel Pump Protection
- Not for Hostile Vehicle Security



4955 Stout Dr. • San Antonio, TX 78219  
TEL: +1 (210) 736 4477 • FAX: +1 (210) 734 6448

Email: [info@slowstop.eu](mailto:info@slowstop.eu)  
[www.slowstop.eu](http://www.slowstop.eu)



QR: Download Spec Sheets  
©2019 SlowStop. All rights reserved. 15-NOV-2018